



LED COACH LANTERN LUMINAIRE

- IES TYPE III DISTRIBUTION – ACRYLIC OPTICS
- 4000 OR 3000 KELVIN CCT
- 1000 mA DRIVER NOMINAL MAXIMUM
- MAXIMUM OF 72 SYSTEM WATTS
- 82 LUMENS PER WATT MINIMUM
- 5500 LUMEN OUTPUT NOMINAL MINIMUM
- L70 GREATER THAN 100,000 HOURS AT 25° C
- 0V – 10V DIMMABLE DRIVER
- MULTI-VOLT OPERATION, 120 – 277V
- 10kV/5kA SURGE PROTECTION DEVICE
- 7-PIN NEMA PHOTOCONTROL RECEPTACLE
- CSA LISTED AND SUITABLE FOR OPERATION 30° C AMBIENT
- ALUMINUM HOUSING
- SLIPFITTER WITH MINIMUM 3 STAINLESS SET SCREWS TO ACCOMMODATE 2-3/8" O.D. POLE TENON
- DARK BRONZE IN COLOR
- TOOLLESS ENTRY
- APPROVED BY SPUC UTILITIES MANAGER AND CITY OF SHAKOPEE CITY ENGINEER

DIRECT EMBEDDED DARK BRONZE
ANODIZED TAPERED ALUMINUM POLE

GRADE



CITY OF
SHAKOPEE
ENGINEERING &
PUBLIC WORKS
DEPTS.

LED COACH LANTERN LIGHTING UNIT

APPROVED: CITY ENGINEER – APPROVED: UTILITIES MANAGER

REVISED:
03-17

DETAIL NO: